

EQUIPMENT & SERVICES INTERNATIONAL, LLC.

5810 POST RD.
EAST GREENWICH, RI 02818
Ph: +1-401-884-2893 - Fx: +1-401-884-1260
E-mail: SALES@ESILLC.CC



TECHNICAL DATA	T-25500M
MAXIMUM LIFTING MOMENT	170,000 FT-LBS
MAXIMUM REACH	T-25500M/2 - 8.03 m (26.34 FT)
	T-25500M/3 - 9.93 m (32.57 FT)
	T-25500M/4 - 11.92 m (39.1 FT)
	T-25500M/5 - 13.98 m (45.86 FT)
	T-25500M/6 - 16.02 m (52.56 FT)
MAXIMUM BOOM ANGLE	75°
SLEWING ANGLE	400°
SLEWING TORQUE	470 FT-LBS
WORKING PRESSURE	4200 PSI
MAXIMUM FLOW	13.2 GPM
GROSS WEIGHT (LBS)	T-25500M/2 - 3,100 KG (6,835 LBS)
	T-25500M/3 - 3,230 KG (7,120 LBS)
	T-25500M/4 - 3,360 KG (7,400 LBS)
	T-25500M/5 - 3,490 KG (7,690 LBS)
	T-25500M/6 - 3,620 KG (7,980 LBS)
OPTIONS: - MANUAL EXTENSIONS - PROPORTIONAL ELECTRIC CONTROLS - HYDRAULIC WINCH - MULTI-PART SHEAVE	

NOTE:
DIMENSIONS IN MILLIMETERS

